



CookTek
MagnaWave™ Systems



Restaurant Equipment Worldwide
Toll Free: 877.FOR.OVEN

International: +1 859.885.1988

Established 1999

PRODUCT:

QTY:

ITEM #:



- Initial charge in 2.5 minutes or less
- Recharges in 60 seconds (avg.)
- No-leak, solid-to-solid phase change material keeps 3 pizzas hot for up to a 45 minute delivery
- Light weight pellet and bag at 3.6 lbs
- Extremely easy to implement with no pellet cord, no maintenance and no extra labor steps
- Charger housing manufactured and designed for easy installation
- Charger does not emit any heat on the locator surface
- Charger performs self-diagnostic features and alerts user in the event of an error
- User-friendly membrane panel and lighted displays are easy to understand and operate
- Charger manufactured and designed to handle exposure to flour, dust, oil, grease and various other food substances found in food establishments
- Charger unit manufactured and designed to operate on a standard countertop or "dropped-in" to a custom shelving unit
- Charger unit operates on a single phase, 15 amps at 120V dedicated outlet or 8 amps for 240V dedicated outlet
- Two year warranty on pellet
- Made in the USA

Shall be a CookTek induction Pizza Thermal Delivery System, Model _____ with a total kW rating of _____. Unit shall come with a powder-coated steel housing, polycarbonate locator tray and membrane panel. The Unit shall be a high power induction heating system intended for the rapid thermal charging of a special heat retaining pellet contained in a CookTek approved insulated delivery bag. The pellet shall be engineered to provide heat to the delivery bag in combination with up to three boxed pizzas, for up to a 45 minute delivery, in a manner that will maintain a defined delivered pizza temperature range. Unit shall operate on _____ power with integral cord and plug supplied.

OPTIONS AT NO CHARGE:

NEMA plug type standard for U.S. and Canadian destinations. All other countries must specify voltage, duty cycle and required NEMA plug configuration. **IMPORTANT:** FlashPak™ Pizza Thermal Delivery System must be used in conjunction with CookTek approved VaporVent™ pizza bags.



Restaurant Equipment Worldwide
Toll Free: 877.FOR.OVEN

International: +1 859.885.1988

Established 1999



MADE IN THE USA

FLASHPAK™ PIZZA THERMAL DELIVERY SYSTEM

PTDS100, PTDS200



COOKTEK
MagnaWave™ Systems



CookTek
MagnaWave Systems

FLASHPAK™ PIZZA THERMAL DELIVERY SYSTEM
PTDS100, PTDS200

FLASHPAK™ PIZZA THERMAL DELIVERY SYSTEM

PTDS100, PTDS200



PRODUCT: QTY: ITEM #:

Dimensions: 16.00 in, 16.00 in, 19.45 in, 15.50 in, 15.50 in, 20.08 in, 16.00 in, 8.16 in, 4.28 in, .78 in, 15.50 in

WARNING LABEL: ONLY USE WITH COOKTEK APPROVED BAGS. PLACE NO FOREIGN OBJECTS ON CHARGER. REMOVE BAG AND TURN OFF CHARGER WHEN UNATTENDED.

POWER CORD

US NSF CE

Model Number	PTDS 100, PTDS 200	
Power requirements	(PTDS100)	120V , 1PH
	(PTDS200)	240V , 1PH
Power consumption		600-1800W
Voltage	(PTDS100)	120V 50/60Hz
	(PTDS200)	240V 50/60Hz
Amperage	(PTDS100)	15 amps
	(PTDS200)	8 amps
Charger dimensions - Base	(Inches)	15.50 x 15.50 x 4.28
Charger dimensions with bag locator	(Inches)	20.08 x 19.45 x 8.16
Weight (Packaged)		17 lbs. (21 lbs.)
Packaging dimensions	(Inches)	24.00 x 23.25 x 13.88
Cord length & Plug type	(PTDS100)	6 ft., NEMA 5-15P
	(PTDS200)	varies
Warranty		One year limited warranty on charger Two year warranty on disc
Cooling clearance		2" front, rear and sides 9" bottom*

* For drop-in installation

Note: Many local codes exist, and it is the Owner and Installer's responsibility to comply with those codes. It's CookTek's policy to continually improve its products, and we reserve the right to change or improve our specifications without notification.

