

# DISHWASHERS

BY LAMBER



Pizzaovens.com

1.877.FOR.OVEN  
367.6836

Since 1999

## DISHWASHER WITH BOOSTER

050FS/050FDPS

### 050FS/050FDPS

Complete with stainless steel top and sides, 208-230 volts single phase.

33" H x 23 3/4" W x 25 3/4" D  
Volts: 230  
Hz: 60  
Amp: 16  
Circuit breaker: 20  
Watt : 3600  
Cycle: 2 min

Clearance: 12 1/2"  
Rack/hr: 30  
Rack size: standard 20" x 20"  
Water consumption / cycle: 1/2 gal.

Included accessories:  
filter kit and insulated control panel  
1 basket for dishes  
1 general basket  
1 cutlery container

- Complete stainless steel construction AISI 304 18/10.
- Double skin.
- Wash tank slanted with rounded edges.
- Washing period cycle 2 minutes.
- Wash and rinse arms in stainless steel.
- Lower and upper rotating wash arms.
- Lower and upper rotating rinse arms
- Constant rinse system 90°.
- Automatic tank loading.
- Thermometers.
- Drains by gravity.
- Rinse aid dispenser.
- Wash detergent pump
- Door opening safety device.
- Security thermostat.
- Extractable control panel for easy maintenance.
- Filter kit (included)
- Total rating: 3650 Watts
- Booster element: 3000 Watts (booster & tank element alternate)
- Booster capacity: 1 gal, 4 l.
- Tank element: 2000 Watts (booster & tank element alternate)
- Tank capacity: 4 1/2 gal., 18 l.
- Water inlet: 1/2 pipe with 3/4 male threaded (hose fitting) Must be connected to hot water only. 120-140 F, 50-60°C
- Required drain: 050FS: 1 1/2" ABS pipe at floor level. Gravity drain. 050FDPS: 1 1/2" ABS at maximum height of 39", 1m. Pumped drain
- Wash temperature: 140° F, 60°C
- Rinse temperature: 180° F, 85°C



Pizzaovens.com

1.877.FOR.OVEN  
367.6836

Since 1999