

COMPACT REFRIGERATORS WORK TOP MODELS



CA3-P



CA5-A



CA4-S



CA6-S



NSF Listed Standard 7
Food Service

SPECIFICATIONS

EXTERIOR FINISH

- FRONT - Stainless steel door(s), fascia
- TOP: S Models - Stainless steel top with removable backsplash
P Models - Stainless steel top with plastic cutting board, removable backsplash
A Models - flat top for under the counter applications
- ENDS - Metallic gray polyester aluminum
- BOTTOM, BACK - Galvanized steel

INTERIOR FINISH

- White polyester aluminum

CABINET

- Door opening breakers are non-conductive, energy saving rigid vinyl
- Heavy-duty 6" legs with 2" adjustment
- Heavy-duty epoxy coated wire shelves are adjustable on 1/2" increments
- 2 1/2" of CFC free polyurethane foam insulation
- Horizontally mounted internal analog thermometer
- Removable 2" backsplash on "P" and "S" models

DOOR

- Stainless steel shell with white polyester aluminum liner
- Self-adjusting, snap-in type black vinyl magnetic door gasket, replaceable without the use of tools
- Chrome plated, self-closing, lift off cam type hinges
- 95 degree hold open feature
- Lifetime safety grip handle

REFRIGERATION

- Hermetic compressor, high starting torque type
- Copper tubed evaporator coil with aluminum fins for maximum cooling
- Coil is plasticized for corrosion resistance
- CFC free, R-134a refrigerant
- Automatic hot gas condensate disposal
- System is tested to maintain 33 to 41 degrees F
- Standard with 8 foot power cord

Model	Crated Wt.	Doors	Cu. Ft.	W/D/H	Volts	Amps	H.P.	Shelves
CA3S/P/A	150	1	6	30.5x28.5x37.5	115/60/1	4.0	1/5	1
CA4S/P/A	265	2	11.5	46.5x28.5x37.5	115/60/1	6.0	1/3	2
CA5S/P/A	275	2	15	61x28.5x37.5	115/60/1	10.0	1/2	2
CA6S/P/A	295	3	17	72x28.5x37.5	115/60/1	10.0	1/2	3

A Models – Height is 35.5



Pizzaovens.com

1.877.FOR.OVEN
367.6836

Since 1999

DIMENSIONAL DRAWINGS

