

FREEZER BASE WORK TABLES

WORK TOP & UNDERCOUNTER MODELS



FWT40S



FWT50S



NSF Listed Standard 7
Food Service



FWT64S



FWT88S

SPECIFICATIONS

EXTERIOR FINISH

- FRONT- Stainless steel door(s) , facia, air grille
- TOP: S Models - stainless steel with 4" backsplash
P Models - stainless steel with 4" backsplash and full size plastic cutting board
G Models - galvanized (used for under the counter)
Note: S and P Models available without backsplash
- ENDS - Aluminum
- BOTTOM, BACK - Galvanized steel

INTERIOR FINISH

- Aluminum

CABINET

- Door opening breakers are non-conductive, rigid vinyl
- Heavy-duty 6" legs with 2" adjustment
- Heavy-duty epoxy coated wire shelves, adjustable on 1/2" increments
- 2 1/2" of CFC free polyurethane foam insulation
- Horizontally mounted internal analog thermometer

DOOR

- Stainless steel shell with aluminum liner
- Self-adjusting, snap-in type black vinyl magnetic door gasket, replaceable without the use of tools
- Chrome plated, self-closing, lift off cam type hinges
- 95 degree hold open feature
- Lifetime safety grip handle

REFRIGERATION

- Hermetic compressor, high starting torque type
- Copper tubed evaporator coil with aluminum fins
- Plasticized coil for corrosion resistance
- CFC free, R-404A refrigerant
- Maintains 0 degrees F storage temperature
- Automatic hot gas condensate disposal
- Standard with 8 foot power cord

Model	Crated Wt.	Doors	Cu. Ft.	W/D/H	Volts	Amps	H.P.	Shelves
				S & P Models				
FWT40S/P/G	365	1	7.7	40x34.75x40	115/60/1	6.0	1/3	2
FWT50S/P/G	415	1	11.4	50x34.75x40	115/60/1	6.0	1/3	2
FWT64S/P/G	440	2	16.9	64x34.75x40	115/60/1	10.0	1/2	4
FWT88S/P/G	530	3	26.2	88x34.75x40	115/60/1	11.0	1/2	6

- G Models - depth is 32.5, height 34"



DIMENSIONAL DRAWINGS

