

DUAL TEMP. REFRIGERATOR/FREEZER


Imperial SERIES



RF55AT




**NSF Listed Standard 7
Food Service**



RF55ATH



RF82AT



RF82ATH

Aluminum Models SPECIFICATIONS

EXTERIOR FINISH

- Front - stainless steel door(s), facia, air grille
- Ends - stainless steel
- Top, Bottom, Back - galvanized steel

INTERIOR FINISH

- Bottom-stainless steel
- Liner-white polyester aluminum

DOOR

- Stainless steel shell with white polyester aluminum liner
- Self-adjusting, snap-in type, black vinyl magnetic door gasket replaceable without the use of tools
- Chrome plated, self-closing, lift off cam type hinges
- 95 degree hold open feature
- Lifetime chrome plated safety grip handles
- Heavy-duty dead bolt locks

CABINET

- Door opening breakers are non-conductive, energy saving rigid vinyl
- Snap-on breaker cap, holds in place the low wattage facia condensation control wire
- Interior light automatically activated by opening the door.
- Heavy duty 6" legs with 2" adjustment
- 2³/₄" of CFC free polyurethane foam insulation reduces compressor run time saving energy
- Heavy-duty epoxy coated wire shelves are adjustable on 1/2" increments
- Color-coded dial thermometer and power indicator light
- Condensate Vaporizer, no plumbing required

REFRIGERATION

- Hermetic compressors, high starting torque type
- Forced air ceiling mount coils with aluminum fins and copper tubing for maximum heat transfer
- Coil is plasticized for corrosion resistance
- CFC free R-134a and R-404A refrigerants
- Systems are tested to an average temperature of 36 to 40 degrees F and -5 to 0 degrees F
- Standard with two 8 foot power cords

MODEL NO.	W/D/H	CU. FT.		DOORS FULL-HALF	SHELVING FULL-HALF	SHIP WT.	AMPS		VOLTAGE		H.P.	
		R	F				R	F	R	F	R	F
RF55AT/ATH	55/32/ 82	21.7	21.7	2 - 4	6 - 8	660	6.2	11	115/ 60/1	115/60/1	1/4	1/2
FR55AT/ATH	55/32/ 82	21.7	21.7	2 - 4	6 - 8	660	6.2	11	115/ 60/1	115/60/1	1/4	1/2
RF82AT/ATH	82/32/ 82	43.7	21.7	3 - 6	9 - 12	855	9.1	11	115/ 60/1	115/60/1	1/3	1/2
FR82AT/ATH	82/32/ 82	21.7	47.3	3 - 6	9 - 12	855	6.2	12	115/ 60/1	115/60/1	1/4	3/4

*RF-left side refrigerator, right side freezer *FR-left side freezer, right side refrigerator NOTE: On 82" wide models the left and center sections are the left side.

- AT-Aluminum, Top Mount
- ATH-Aluminum, Top Mount, Half Doors

DIMENSIONAL DRAWINGS

