

REFRIGERATED PREPARATION TABLES



NSF Listed Standard 7
Food Service



RPT40P



RPT88S



RPT50S



RPT64P

SPECIFICATIONS

EXTERIOR FINISH

- FRONT - Stainless steel door(s), fascia, air grille
- TOP: S Models - stainless steel
P Models - stainless steel with plastic cutting board
MB Models - stainless steel with marble cutting board
- ENDS - Aluminum
- BOTTOM, BACK - Galvanized steel

INTERIOR FINISH

- Aluminum

CABINET

- Door opening breakers are non-conductive, rigid vinyl
- Heavy-duty 6" legs with 2" adjustment
- Heavy-duty epoxy coated wire shelves, adjustable on 1/2" increments
- 2 1/2" of CFC free polyurethane foam insulation
- Removable pan bars: RPT40 (4) RPT64 (6)
RPT50 (4) RPT88 (8)
- Horizontally mounted internal analog thermometer
- **Food pans not included.**

DOOR

- Stainless steel shell with aluminum liner
- Self-adjusting, snap-in type black vinyl magnetic door gasket, replaceable without the use of tools
- Chrome plated, self-closing, lift off cam type hinges
- 95 degree hold open feature
- Lifetime safety grip handle

REFRIGERATION

- Hermetic compressor, high starting torque type
- Copper tubed evaporator coil with aluminum fins
- Cold wall design in the refrigerated rail minimizes product dehydration
- Force air design in the storage compartment
- One piece refrigerated rail, eliminates spillage into the storage compartment
- CFC free, R-134a refrigerant
- Maintains temperatures between 33 to 41 degrees F
- Automatic hot gas condensate disposal
- Standard with 8 foot power cord

Model	Crated Wt.	Doors	Cu. Ft.	W/D/H	Volts	Amps	H.P.	Shelves
RPT40S/P	400	1	7.7	40x34.5x46	115/60/1	5.7	1/4	2
RPT50S/P	450	1	11.4	50x34.5x46	115/60/1	5.7	1/4	2
RPT64S/P	490	2	17.0	64x34.5x46	115/60/1	6.0	1/3	4
RPT88S/P	525	3	26.0	88x34.5x46	115/60/1	8.0	1/2	6



DIMENSIONAL DRAWINGS

