

#SM-4 "Even Flow" Full Size Convection Oven

When Dependability is a MUST- Deluxe is your Answer

Versatility • **Quality** • **Performance**





Model HSM-4/P-8S

"Oven/Proofer Combination"

Proofer Features:

- 8 Pan Capacity (18"x 26")
- · Individual Heat and Humidity Controls
- · Circulating Blower
- Visible Humidity Pan-Trouble-Free
- 60 Minute Electro-Mechanical Timer
- Lifeline Hinges / Positive Closure
- · Stainless Steel Interior & Exterior

Options:

Oven: Internal Steam or Steam Generator

Proofer: Auto-Fill Humidity Pan
MADE IN USA







"Counter-Model"

Oven Features:

- Unique Design Insures Even Baking 4 Pan Capacity (18"x 26")
- Lifeline Hinges / Positive Closure
- 2-Speed Fan
- Field Reversible Full-View Heat Reflective Glass Door – Fully Gasketed
- Solid State Thermostat 100°-450°
- Stainless Steel Interior & Exterior
- 4" Ajustable Spacing
- No Venting Required In Most Areas**

(** Check local codes)

SPECIFICATIONS

Dimensions

HSM-4 (Oven Only)

Exterior:

31- 1/2" Width 32- 1/2" Depth

31-1/2" Height

Interior:

18-1/2" Width

28" Depth

17-3/4" Height

HSM-4/P-8S (Oven-Proofer)

Overall Exterior:

31-1/2" Width 32-1/2" Depth


71-1/2" Height (On 4" costers)

Proofer Interior:


19" Width


29" Depth

27" Height



COUNTER MODEL HSM-4





FRONT

ELECTRICAL

HSM-4 (Oven Only): 7520 watts • 8 kw • 50/60 Hz

HSM-4/P-8S (Oven Proofer Combination): 9000 watts • 9 kw • 50/60 Hz

MODEL#	VOLTAGE AND PHASE	NEUTRAL	TOTAL LOAD (AMPS)
HSM-4	120/208-1-50/60	REQUIRED	36.0
(Oven Only)	120/208-3-50/60	REQUIRED	30.0
	120/240-1-50/60	REQUIRED	31.0
	120/240-3-50/60	REQUIRED	26.0
HSM-4/P-8S	120/208-1-50/60	REQUIRED	44.0
(Combination)	120/208-3-50/60	REQUIRED	38.0
	120/240-1-50/60	REQUIRED	38.0
	120/240-3-50/60	REQUIRED	33.0

** Please Specify Electrical Requirements When Ordering

Proofer Only: 120V, 1ph., 50/60 Hz, 15 Amps

One Full Year on all parts from date of purchase.

For general sales and engineering information only. All units are subject to change without notice. Please consult factory for certified specifications.

"Even Flow" **Full Size Convection Oven**

(Oven/Proofer Combination)

Approximately 350 lbs. Oven Only 500 lbs. Oven/Proofer 130 lbs. CR-Base



