



UB-6T Tabletop V-Air® Oven STANDARD FEATURES:

- V-Air® system
- Stainless steel construction
- Stainless steel legs (6")
- Full view tempered glass door
- Silicone rubber gasket on door
- Flush mount, lift off, no sag door
- Steam vent

OPTIONS:

- Internal Steam
- Cook'n Hold
- Solid Door
- Two Speed Fan
- Large Vent
- Meat Probe
- Cart with Panslides

CONSTRUCTION:

- Welded stainless steel utilizing 16 and 18 gauge
- Minimum of 2" insulation
- Control panel accessible through front and side of unit
- Heating elements accessible inside of cabinet and through side

CONTROLS:

- Solid state controls
- Indicator light for thermostat
- Four speed fan switch
- Microswitch fan motor cut-off

DOOR SWING: • Oven: 24-1/4"

CLEARANCE: • Allow four inches on each side and back of unit.

SERVICE CONNECTIONS:

- Unit is shipped from factory to be hard wired on site.
Single phase uses four wire system.
Three phase uses five wire system.
- 120/208 or 120/240 Volt single or three phase is standard.
Please specify at time of order.
- Two 4,200 Watt heating elements are mounted in the sidewalls.
- If the internal steam option is selected, the waterline should be 1/4". A water softening system should be used to minimize mineral build-up.

SHIPPING WEIGHT: • 400 Pounds, FOB Menominee, MI 49858

DIMENSIONS:

	Height	Width	Depth
Exterior	50"	32"	34-3/8"
Interior	28-1/2"	18-1/4"	28-1/4"

CAPACITY:

	18"x26" Sheet Pans	13"x18" Sheet Pans	Spacing
Oven	6	12	4-1/4"

ELECTRICAL:

Amp Draw	120/208/1	120/208/3	120/240/1	120/240/3
L1	45	27	39	22
L2	41	35	35	31
L3	n/a	20	n/a	18

